


Current Transducer HXS 20-NP/SP30

For the electronic measurement of currents: DC, AC, pulsed..., with galvanic separation between the primary circuit and the secondary circuit.



All data are given with $R_L = 10\text{ k}\Omega$

$I_{PN} = 5, 10, 20\text{ A}$



Electrical data

I_{PN}	Primary nominal RMS current	± 20	A
I_{PM}	Primary current, measuring range	± 60	A
S_N	Nominal sensitivity	0.625	V / I_{PN}
U_{out}	Output voltage (Analog) @ I_P	$U_{OE} \pm (0.625 \cdot I_P / I_{PN})$	V
U_{ref}	Reference voltage ¹⁾ Output voltage	2.5 ± 0.025	V
	Output impedance	typ. 200	Ω
	Load impedance	200	k Ω
R_L	Load resistance	2	k Ω
R_{out}	Output internal resistance	< 5	Ω
C_L	Load capacitance ($\pm 20\%$)	4.7	nF
U_C	Supply voltage ($\pm 5\%$) ²⁾	5	V
I_C	Current consumption @ $U_C = 5\text{ V}$	19	mA

Accuracy - Dynamic performance data

ε	Error ³⁾ @ $I_{PN}, T_A = 25\text{ }^\circ\text{C}$	± 1	%
ε_L	Linearity error 0 ... I_{PN}	± 0.5	%
	0 ... $3 \times I_{PN}$	± 1	%
TCU_{OE}	Temperature of coefficient of U_{OE} (+25 ... 85 $^\circ\text{C}$)	± 0.4	mV/K
	(-40 ... +25 $^\circ\text{C}$)	± 0.525	mV/K
TCU_{ref}	Temperature of coefficient of U_{ref} (+25 ... 85 $^\circ\text{C}$)	± 0.01	%/K
	(-40 ... +25 $^\circ\text{C}$)	± 0.015	%/K
TCU_{OE}/U_{ref}	Temperature coefficient of U_{OE}/U_{ref}	± 0.15	mV/K
TCS	Temperature of coefficient of S	$\pm 0.07\%$ of reading	/K
U_{OE}	Electrical offset voltage @ $I_P = 0, T_A = 25\text{ }^\circ\text{C}$	$U_{ref} \pm 0.0125$	V
U_{OM}	Magnetic offset voltage @ $I_P = 0$		
	after an overload of $3 \times I_{PN}$	± 1.2	%
t_{D10}	Delay time to 10 % of the final output value for I_{PN} step	< 3	μs
t_{D90}	Delay time to 90 % of the final output value for I_{PN} step ⁴⁾	< 5	μs
U_{no}	Output voltage noise (DC ... 10 kHz)	< 20	mVpp
	(DC ... 1 MHz)	< 40	mVpp
BW	Frequency bandwidth (-3 dB) ⁵⁾	DC ... 50	kHz

- Notes:**
- 1) It is possible to overdrive U_{ref} with an external reference voltage between 1.5 - 2.8 V providing its ability to sink or source approx. 5 mA
 - 2) Maximum supply voltage (not operating) < 6.5 V
 - 3) Excluding offset and magnetic offset voltage
 - 4) For a $di/dt = 50\text{ A}/\mu\text{s}$
 - 5) Small signal only to avoid excessive heatings of the magnetic core.

Features

- Hall effect measuring principle
- Multirange current transducer through PCB pattern lay-out
- Galvanic separation between primary and secondary circuit
- Insulation test voltage 3500 V
- Extremely low profile < 11 mm
- Fixed offset & sensitivity
- Low power consumption
- Single power supply +5 V
- Insulating plastic case recognized according to UL 94-V0.

Special feature

- Designed to avoid heating.

Advantages

- Small size and space saving
- Only one design for wide current ratings range
- High immunity to external interference
- U_{ref} IN/OUT.

Application

- AC variable speed drives and servo motor drives
- Static converters for DC motor drives
- Battery supplied applications
- Uninterruptible Power Supplies (UPS)
- Switched Mode Power Supplies (SMPS)
- Power supplies for welding applications.

Application domain

- Industrial.

Current Transducer HXS 20-NP/SP30

General data

T_A	Ambient operating temperature	-40 ... +85	°C
$T_{A\text{st}}$	Ambient storage temperature	-40 ... +85	°C
m	Mass	10	g
	Standards	EN 50178: 1997	

Insulation coordination

U_d	RMS voltage for AC insulation test, 50 Hz, 1 min	3.5	kV
		Min	
d_{Cp}	Creepage distance	7.48	mm
d_{Cl}	Clearance	6.6	mm
CTI	Comparative tracking index (group I)	> 600	

Applications examples

According to EN 50178, IEC 61010-1 and UL 508 standards and following conditions:

- Over voltage category OV 3
- Pollution degree PD2
- Non-uniform field

	EN 50178	IEC 61010-1
d_{Cp}, d_{Cl}	Rated insulation voltage	Nominal voltage
Basic insulation	600 V	600 V
Reinforced insulation	300 V	150 V

Safety

This transducer must be used in limited-energy secondary circuits according to IEC 61010-1.



This transducer must be used in electric/electronic equipment with respect to applicable standards and safety requirements in accordance with the manufacturer's operating instructions.




Caution, risk of electrical shock

When operating the transducer, certain parts of the module can carry hazardous voltage (eg. primary busbar, power supply). Ignoring this warning can lead to injury and/or cause serious damage.

This transducer is a build-in device, whose conducting parts must be inaccessible after installation. A protective housing or additional shield could be used.

Main supply must be able to be disconnected.

Dimensions HXS 20-NP/SP30 (in mm)



Number of primary turns	Primary RMS current		Primary resistance R_p [mΩ]	Primary insertion inductance L_p [μH]	Recommended PCB connections
	Nominal I_{PN} [A]	Maximum I_p [A]			
1	20	60	0.05	0.029	IN 1 3 5 7 ○ ○ ○ ○ ○ ○ ○ ○ 2 4 6 8 OUT
2	10	30	0.2	0.12	IN 1 3 5 7 ○ ○ ○ ○ ○ ○ ○ ○ 2 4 6 8 OUT
4	5	15	1	0.46	IN 1 3 5 7 ○ ○ ○ ○ ○ ○ ○ ○ 2 4 6 8 OUT

Mechanical characteristics

- General tolerance ± 0.2 mm
- Transducer fastening & connection of primary jumper 8 pins 1.2 mm × 1.2 mm (corner R 0.4 mm)
- Transducer fastening & connection of secondary pin 4 pins 0.5 × 0.25 mm

Recommended PCB hole

- Primary PCB hole $\varnothing 1.5$ mm
- Secondary PCB hole $\varnothing 0.7$ mm

Remarks

- U_{out} is positive when I_p flows from terminals 1, 3, 5, 7 (IN) to terminals 2, 4, 6, 8 (OUT).
- Temperature of the primary conductor should not exceed 100 °C.
- Installation of the transducer must be done, unless otherwise specified on the datasheet, according to LEM Transducer Generic Mounting Rules. Please refer to LEM document N°ANE120504 available on our Web site: <https://www.lem.com/en/file/3137/download>